## NSN 6625-01-346-0064

Ammeter - Page 1 of 2

**Circuit Current For Which Designed:** 

White single indicator single range



View Online at https://aerobasegroup.com/nsn/6625-01-346-0064

Dielectric Withstanding Voltage In Volts:
2300.0
Overall Length:
5.710 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.380 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.380 inches
Overall Height:
4.330 inches
Overall Width:
4.330 inches
Scale Division Quantity:
60 single indicator single range
Mounting Stud Length:
0.625 inches
Environmental Protection:
Dust resistant and watertight
Furnished Items And Quantity:
Nut 8; washer 6
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1000.0 ohms per volt
Dial Scale Marking Color:
Black single indicator single range and red single indicator single range
Accuracy In Percent:
-1.5/+1.5 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
3.790 inches
Meter Body Diameter Behind Mounting Flange:
3.970 inches
Movement Type:
Moving coil, permanent magnet
Background Color:

## NSN 6625-01-346-0064

Ammeter - Page 2 of 2



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+600.0 amperes, ac single indicator single range
Mounting Stud Diameter:
0.250 inches
Features Provided:
Nonglare glass and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Sign at left terminal; red line at 480a
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Electrical, electronic properties measuring and test instruments
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0