NSN 6625-01-346-7934

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-346-7934

Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.850 inches
Mounting Hole Diameter:
Between 0.143 inches and 0.157 inches
Scale Division Quantity:
40 single indicator single range
Overall Diameter:
3.510 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Nut 7; washer 7
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
2.800 inches
2.800 inches Movement Type:
2.800 inches Movement Type: Moving coil, permanent magnet
2.800 inches Movement Type: Moving coil, permanent magnet Background Color:
2.800 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
2.800 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color:

NSN 6625-01-346-7934 Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-20.0/+20.0 amperes, dc single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/12 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A310a0