

View Online at <https://aerobasegroup.com/nsn/6625-01-346-7935>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

800.0

**Overall Length:**

2.645 inches

**Overall Height:**

4.090 inches

**Overall Width:**

4.640 inches

**Mounting Stud Length:**

Between 0.540 inches and 0.580 inches

**Distance Between Mounting Facility Centers:**

Between 1.240 inches and 1.260 inches

**Furnished Items And Quantity:**

Nut 4; washer 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

1150.0 ohms

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.370 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 2.795 inches and 2.825 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0/+50.0 microamperes, dc single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic phenolic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0