

View Online at <https://aerobasegroup.com/nsn/6625-01-347-9380>

Width:

Between 4.250 inches and 4.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.346 inches and 3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.346 inches and 3.406 inches

Length:

7.500 inches

Current Type:

Ac

Ac Voltage Rating:

450.0 volts

Frequency Rating:

60.0 hertz

Mounting Stud Length:

Between 0.500 inches and 0.750 inches

Mounting Flange Length:

Between 4.250 inches and 4.500 inches

Mounting Flange Width:

Between 4.250 inches and 4.500 inches

Contact Quantity:

3

Contact Type:

Threaded stud

Usage Design:

Panel mounted

Presentation Type:

Indicator light

Mounting Arrangement Style:

Four hole/stud rectangular/square

Mounting Flange Diameter:

1.000 inches

Electrical Connection Quantity:

3

Mounting Facility Type And Quantity:

1 flange and 4 threaded stud

Mounting Stud Diameter:

0.250 inches

Features Provided:

Lamp socket

Case Material:

Plastic or steel

Phase:

Two

Height:

Between 4.250 inches and 4.500 inches

Test Data Document:

81349-mil-i-16103 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-i-16103 government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A534h0