

View Online at <https://aerobasegroup.com/nsn/6625-01-347-9380>

**Width:**

Between 4.250 inches and 4.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 3.346 inches and 3.406 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 3.346 inches and 3.406 inches

**Length:**

7.500 inches

**Current Type:**

Ac

**Ac Voltage Rating:**

450.0 volts

**Frequency Rating:**

60.0 hertz

**Mounting Stud Length:**

Between 0.500 inches and 0.750 inches

**Mounting Flange Length:**

Between 4.250 inches and 4.500 inches

**Mounting Flange Width:**

Between 4.250 inches and 4.500 inches

**Contact Quantity:**

3

**Contact Type:**

Threaded stud

**Usage Design:**

Panel mounted

**Presentation Type:**

Indicator light

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Mounting Flange Diameter:**

1.000 inches

**Electrical Connection Quantity:**

3

**Mounting Facility Type And Quantity:**

1 flange and 4 threaded stud

**Mounting Stud Diameter:**

0.250 inches

**Features Provided:**

Lamp socket

**Case Material:**

Plastic or steel

**Phase:**

Two

**Height:**

Between 4.250 inches and 4.500 inches

**Test Data Document:**

81349-mil-i-16103 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-i-16103 government specification

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A534h0