NSN 6625-01-349-0259

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-349-0259

Circuit Current For Which Decigned
Circuit Current For Which Designed: Dc
Overall Length: 4.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.380 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.380 inches
Overall Height:
Between 4.407 inches and 4.437 inches
Overall Width:
Between 4,407 inches and 4,437 inches
Mounting Hole Diameter:
0.250 inches
Scale Division Quantity:
60 single indicator single range
Environmental Protection:
Shock resistant and vibration resistant
Furnished Items And Quantity:
Nut 8
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.5/+1.5 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.813 inches
Meter Body Diameter Behind Mounting Flange:
3.960 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External

NSN 6625-01-349-0259

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+600.0 amperes, dc single indicator single range

Features Provided:

External shunting and zero adjuster

Criticality Code Justification:

Zzzy

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo4426

Material:

Steel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing

and testing specifications available at the dla icp.

Shelf Life:

N/a

```
Unit Of Measure:
```

--

```
Demilitarization:
```

No

Fiig:

A310a0