

View Online at <https://aerobasegroup.com/nsn/6625-01-350-1464>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

420.0 millimeters

Overall Height:

89.0 millimeters

Overall Width:

455.0 millimeters

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Furnished Items And Quantity:

Rack slide kit 1

Indicator Type:

Digital display

Installation Design:

Rack

Power Source:

External

Display Type:

Gas discharge tube

Display Digit Quantity:

6-1/2

Measurement Range:

+0.0/+1000.0 volts, dc single indicator 1st range+0.0/+1000.0 volts, ac single indicator 2nd range+0.0/+1.0 megohms single indicator 3rd range

Accuracy Rating:

Porm 0.01 pct of reading porm 1 digit single indicator 1st rangeform 7 pct of reading porm 200 digits single indicator 2nd rangeform 0.06 pct of reading porm 1 digit single indicator 3rd range

Display Color:

Red single indicator all ranges

Circuit Attachment Method And Quantity:

6 banana jack and 6 binding post

Operating Voltage Rating In Volts:

Between 105.0 ac and 255.0 ac

Interface Compatibility:

leee-488

Special Features:

Input power 105-127 or 205-255vac

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rack

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0