

View Online at <https://aerobasegroup.com/nsn/6625-01-350-5475>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

1.251 inches

Scale Division Quantity:

20 single indicator single range

Overall Diameter:

1.250 inches

Environmental Protection:

Shock resistant and vibration resistant

End Application:

6115-01-317-8680 generator, direct current

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.375 inches

Meter Body Diameter Behind Mounting Flange:

Between 0.985 inches and 1.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+20.0/+40.0 volts, dc single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0