## NSN 6625-01-355-2830

Field Strength Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-355-2830

Circuit Current For Which Designed:
Ac or dc
Overall Depth:
6.000 inches
Overall Length:
9.000 inches
Overall Width:
8.500 inches
Frequency Rating:
Between 50.0 hertz and 60.0 hertz
End Application:
Peacekeeper and servielance programs
Indicator Type:
Dial w/pointer
Installation Design:
Bench
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-5.0/+5.0 at full scale single indicator all ranges
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Scale Graduation Type:
Nonlinear single indicator all ranges
Measurement Range:
-0.1/+0.1 volts per meter single indicator 1st range-0.2/+0.2 volts per meter single indicator 2nd range-0.5/+0.5 volts per meter single
indicator 3rd range-1.0/+1.0 volts per meter single indicator 4th range-2.0/+2.0 volts per meter single indicator 5th range-5.0/+5.0 volts per
meter single indicator 6th range-10.0/+10.0 volts per meter single indicator 7th range
Scale Selection Method:
Switch
Features Provided:
Portable and internal battery accommodation
Circuit Attachment Method And Quantity:
1 sensor
Operating Voltage Rating In Volts:
Between 90.0 ac and 260.0 ac and 6.0 dc
Phase:
Single
Nuclear Hardness Critical Feature:

Portable

Nonhardened

Style Designator:

## NSN 6625-01-355-2830

Field Strength Meter - Page 2 of 2



Unit	Of	Issue	Weight:
------	----	-------	---------

1.00 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0