

View Online at <https://aerobasegroup.com/nsn/6625-01-355-4778>

Ac Voltage Rating:

110.0 volts and 128.0 volts and 220.0 volts and 238.0 volts

Frequency Rating:

Between 50.0 hertz and 100.0 hertz

Capacitance Scale Range:

+0.0/+100.0 microfarads

Capacitance Scaleaccuracy Rating In Percent:

+0.0/+0.3

Err Default:

Err default

Dissipation Factor In Percent:

+0.001/+500.000

Inductance Scale Range:

+0.0/+32000.0 henry

Inductance Scaleaccuracy Rating In Percent:

+0.0/+0.3

Resistance Scale Range:

+0.0/+200.0 megohms

Resistance Scaleaccuracy Rating In Percent:

+0.0/+0.3

Extra Long Reference Number:

Pm6303/008-pm9541/00-pm9542-pm9542smd

Phase:

Single

Functional Description:

Determine the value, electric dimension and equalivent circuit of passive components

Supplementary Features:

Lcd display; automatic operation; displays component value, measurement units and equivalent circuit; selectionof 9 different parameters; 2 or 4 wireconnections; smd testing via optional test attachment; test set contains, pm6303/008 automatic rcl meter, pm9541/00 four wire test cable, pm9542 rcl test adapter, pm9542smd smd adapter for pm9542

Reference Number Differentiating Characteristics:

As differentiated by elrn

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T228-d