

View Online at <https://aerobasegroup.com/nsn/6625-01-355-7282>

Circuit Current For Which Designed:

Dc

Overall Length:

7.218 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.422 inches

Overall Width:

4.422 inches

Mounting Hole Diameter:

0.312 inches

Scale Division Quantity:

10 single indicator single range

Environmental Protection:

Shock resistant and splash proof and vibration resistant

End Application:

Arleigh burke class ddg, ticondaroga class c (47)oliver perry class ffg, seawolf class ssn, ohio class ssn, nimitz class cvn, los angeles class ssn, spruance class dd(963)deep submergence systems programs (dssp)

Furnished Items And Quantity:

Nut 6; washer 12

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range and green single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.750 inches

Meter Body Diameter Behind Mounting Flange:

3.960 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Features Provided:

Zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Weapon system essential

Special Markings:

Green line at zero

Material:

Steel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0