NSN 6625-01-355-8906

Instrument Shunt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-355-8906

Overall Length: 7.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 6.875 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches Overall Width: 2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location: Top
7.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 6.875 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches Overall Width: 2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Center To Center Distance Between Mounting Facilities Parallel To Length: 6.875 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches Overall Width: 2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches Overall Width: 2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches Overall Width: 2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
1.500 inches Overall Width: 2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Overall Width: 2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
2.620 inches Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Unthreaded Mounting Hole Diameter: 0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
0.280 inches Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Usage Design: External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
External Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Element Material: Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Aluminum alloy Mounting Method: Unthreaded hole Terminal Location:
Mounting Method: Unthreaded hole Terminal Location:
Unthreaded hole Terminal Location:
Terminal Location:
Тор
Voltage Drop In Millivolts:
50.0
Special Features:
Handling shock: four foot free drop onto concrete floor
Supplementary Features:
Fault currents will be limited by a current overload sensor
Terminal Type And Quantity:
4 screw
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A33500