

View Online at <https://aerobasegroup.com/nsn/6625-01-356-6259>

**Circuit Current For Which Designed:**

Ac and dc

**Overall Depth:**

1.750 inches

**Overall Length:**

6.125 inches

**Overall Width:**

3.625 inches

**Environmental Protection:**

Dust resistant and fungus resistant and water resistant

**Furnished Items And Quantity:**

Carrying case; electrode extension; extension adapter; 0.1 ohm shunt; 0.001 ohm shunt

**Indicator Type:**

Digital display

**Installation Design:**

Hand held

**Power Source:**

Internal

**Display Type:**

Liquid crystal

**Display Digit Quantity:**

3-1/2

**Measurement Range:**

+0.0/+20.0 amperes, dc single indicator 1st range+0.0/+20.0 millivolts, dc single indicator 2nd range+0.0/+200.0 millivolts, dc single indicator 3rd range+0.0/+200.0 ohms single indicator 4th range+0.0/+600.0 volts, ac single indicator 5th range+0.0/+2.0 volts, dc single indicator 6th range+0.0/+200.0 volts, dc single indicator 7th range

**Scale Selection Method:**

Switch

**Features Provided:**

External shunting and internal battery accommodation

**Accuracy Rating:**

1 pct of rdg porm 1 digit single indicator 1st range1 pct of rdg porm 1 digit single indicator 2nd range1 pct of rdg porm 1 digit single indicator 3rd range2 pct of rdg porm 1 digit single indicator 4th range3 pct of rdg porm 1 digit single indicator 5th range1 pct of rdg porm 1 digit single indicator 6th range1 pct of rdg porm 1 digit single indicator 7th range

**Circuit Attachment Method And Quantity:**

3 banana plug

**Operating Voltage Rating In Volts:**

9.0 dc

**Special Features:**

Push to hold reading button; user selectable input resistance switch, 10, 25, 50, 100, 200 megohms

**Functional Description:**

Used for corrosion and cathodic protection

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0