

View Online at <https://aerobasegroup.com/nsn/6625-01-356-6259>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

1.750 inches

Overall Length:

6.125 inches

Overall Width:

3.625 inches

Environmental Protection:

Dust resistant and fungus resistant and water resistant

Furnished Items And Quantity:

Carrying case; electrode extension; extension adapter; 0.1 ohm shunt; 0.001 ohm shunt

Indicator Type:

Digital display

Installation Design:

Hand held

Power Source:

Internal

Display Type:

Liquid crystal

Display Digit Quantity:

3-1/2

Measurement Range:

+0.0/+20.0 amperes, dc single indicator 1st range+0.0/+20.0 millivolts, dc single indicator 2nd range+0.0/+200.0 millivolts, dc single indicator 3rd range+0.0/+200.0 ohms single indicator 4th range+0.0/+600.0 volts, ac single indicator 5th range+0.0/+2.0 volts, dc single indicator 6th range+0.0/+200.0 volts, dc single indicator 7th range

Scale Selection Method:

Switch

Features Provided:

External shunting and internal battery accommodation

Accuracy Rating:

1 pct of rdg porm 1 digit single indicator 1st range1 pct of rdg porm 1 digit single indicator 2nd range1 pct of rdg porm 1 digit single indicator 3rd range2 pct of rdg porm 1 digit single indicator 4th range3 pct of rdg porm 1 digit single indicator 5th range1 pct of rdg porm 1 digit single indicator 6th range1 pct of rdg porm 1 digit single indicator 7th range

Circuit Attachment Method And Quantity:

3 banana plug

Operating Voltage Rating In Volts:

9.0 dc

Special Features:

Push to hold reading button; user selectable input resistance switch, 10, 25, 50, 100, 200 megohms

Functional Description:

Used for corrosion and cathodic protection

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0