

View Online at <https://aerobasegroup.com/nsn/6625-01-356-6950>

Overall Depth:

610.0 millimeters

Overall Height:

240.0 millimeters

Overall Width:

430.0 millimeters

Ac Voltage Rating:

100.0 volts and 240.0 volts

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

End Application:

Lgm118a missile

Unpackaged Unit Weight:

30.2 kilograms

Mounting Method:

Rack

Instrument Calibration Range:

0.0 to 1100vdc

Calibration Range Quantity:

4

Calibration Accuracy Rating:

Porm 1.5 ppm plus 5 microvolts at11v to porm 2.5 ppm plus 400 microvolts at 1100v

Phase:

Single

Special Features:

leee488 & rs-232c & boost interfaces; rear outputs; 4 output ranges, 0 to 11vdc, 11 to 22vdc, 22 to 275vdc, 275 to 1100vdc; output current 0 to 60 milliamps up to 22vdc, 0 to 25 milliamps up to 1100vdc; has program module for presetting for test sequences; 40 character alpha-numeric vacuum fluorescent display; power consumption 84 watts in standby, 145 watts

Supplementary Features:

Option mm is rackmounting kits, r/n m08-205-600 and m00-280-610

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T263-b