

View Online at <https://aerobasegroup.com/nsn/6625-01-356-9558>

**Overall Depth:**

25.250 inches

**Overall Height:**

8.750 inches

**Overall Width:**

19.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 48.0 hertz and 66.0 hertz

**Accessory Components And Quantity:**

Ac power cord 1; rackmount kit 1

**Voltage Rating:**

115.0 volts and 230.0 volts

**Beam Quantity:**

2

**Mounting Method:**

Rack

**Sweep Circuits:**

Included

**Sweep Frequency Range:**

+250.0/+500.0 megahertz

**Single Trigger Sweep Duration:**

Between 0.0001 microseconds and 0.0003 microseconds

**Trigger Sweep Voltage Amplitude Rating:**

Between 1.0 volts and 10.0 volts

**Trigger Sweep Polarity Switch:**

Included

**Amplifier Deflection Sensitivity Provision:**

Provided

**Vertical Deflection Sensitivity Voltage Rating:**

1.0 millivolts peak to peak per centimeter and 5.0 millivolts peak to peak per centimeter

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Calibrated Screen Scale:**

Included

**Camera Recording Device Accommodation:**

Provided

**Phase:**

Single

**Special Features:**

C2 gigasample/second, two channel digitizing, 8k memory/channel, automatic measurements, autoscaling, cursors, color display, scrolling, zoom and memory bar, advance logic triggering, ieee-488 interface bus

**Supplementary Features:**

Option 909 is rackmount with handles kit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T320-g