

View Online at <https://aerobasegroup.com/nsn/6625-01-356-9558>

Overall Depth:

25.250 inches

Overall Height:

8.750 inches

Overall Width:

19.000 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 66.0 hertz

Accessory Components And Quantity:

Ac power cord 1; rackmount kit 1

Voltage Rating:

115.0 volts and 230.0 volts

Beam Quantity:

2

Mounting Method:

Rack

Sweep Circuits:

Included

Sweep Frequency Range:

+250.0/+500.0 megahertz

Single Trigger Sweep Duration:

Between 0.0001 microseconds and 0.0003 microseconds

Trigger Sweep Voltage Amplitude Rating:

Between 1.0 volts and 10.0 volts

Trigger Sweep Polarity Switch:

Included

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

1.0 millivolts peak to peak per centimeter and 5.0 millivolts peak to peak per centimeter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Included

Camera Recording Device Accommodation:

Provided

Phase:

Single

Special Features:

C2 gigasample/second, two channel digitizing, 8k memory/channel, automatic measurements, autoscaling, cursors, color display, scrolling, zoom and memory bar, advance logic triggering, ieee-488 interface bus

Supplementary Features:

Option 909 is rackmount with handles kit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g