

View Online at <https://aerobasegroup.com/nsn/6625-01-357-2023>

Overall Depth:

Between 18.900 inches and 22.200 inches

Overall Height:

Between 6.300 inches and 7.500 inches

Overall Width:

13.300 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

End Application:

Bu 15 gats and general use

Voltage Rating:

Between 115.0 volts and 250.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in v/cm both axes

Mounting Method:

Any acceptable

Accuracy Range In Percent:

-2.0/+2.0

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal

Sweep Frequency Range:

+0.2/+200000000.0 hertz

Single Trigger Sweep Duration:

0.1 nanoseconds

Trigger Sweep Polarity Switch:

Not included

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

2.0 microvolts rms per centimeter and 5.0 volts rms per centimeter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Not provided

Amplifier Input Impedance Rating Provision:

Not provided

Calibrated Screen Scale:

Included

Trace Storage Tube:

Included

Camera Recording Device Accommodation:

Provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-g