Current-voltage Standard - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-357-5055

Terminal Quantity:

8

Terminal Type:

Banana plug

Overall Depth:

22.200 inches

Overall Height:

7.000 inches

Overall Width:

17.900 inches

Ac Voltage Rating:

110.0 volts and 220.0 volts

Portability:

Portable

Unit Type:

Encased

Output Voltage Rating:

Between 1.0 millivolts and 1100.0 volts

Output Current Rating:

Between 1.0 milliamperes and 1.0 amperes

Electromotive Force Production Method:

Electronic

Output Accuracy Rating In Percent:

+0.015/+0.450

Warm-up Time For Maximum Accuracy In Minutes:

120.0

Protective Device Type:

Fuse

Phase:

Single

Special Features:

This item supplied to agmc for ii/iii pmels has increased accuracy over the commercial off the shelf item. The basic instrument consists of a mainframe to which has been added option 20 (ac voltage function); option 30 (calibration sources of dc current, ac current and resistance). The unit can be either bench or rack mounted. The ac voltage frequency range is 10hz-1mhz. The ac current frequency range is 40hz-5khz

```
Entry Date:
```

93-06-23

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T263-k