

View Online at <https://aerobasegroup.com/nsn/6625-01-357-9768>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

4.152 inches

Overall Height:

1.284 inches

Overall Width:

Between 3.973 inches and 4.027 inches

Mounting Hole Diameter:

0.149 inches

Scale Division Quantity:

12 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

Between 3.773 inches and 3.787 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.430 inches

Meter Body Width Behind Mounting Flange:

3.430 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

60; 30; 0; 30; 60; turn rate; deg/min

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

1.284 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Special Features:

Ruggedized

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0