

View Online at <https://aerobasegroup.com/nsn/6625-01-359-9511>

Current Type:

Ac/dc

Frequency Rating:

100.0 megahertz

End Application:

Gcf-w1002-ros

Electrical Connection Type:

Bnc

Internal Battery Accommodation:

Included

Voltage Rating:

5.0 pounds per hour with retaining chain

Electrical Connection Quantity:

3

Mounting Method:

Rack

Measurement Type:

Frequency and ratio

Frequency Range:

+0.000/+100.000 megahertz f1 input ratio and +0.000/+100.000 megahertz f2 input ratio

Accuracy Rating:

Time base error

Gate Time:

Between 10.0 microseconds and 60.0 microseconds

Sensitivity Rating:

10 mv rms sinewave to 10 mhz; 25 mv rms sinewave to 100 mhz; 75 mv peak to peak pulse at pulse width of 5 ns; 20 mv rms sinewave to 10 mhz; 50 mv rms to 100 mhz; 150 mv peak to peak at a pulse width of 5 ns

Ratio Display:

8-digital led display

Internal Calibration Feature:

Not included

Display Type:

Light emitting diode (I.E.D.).

Display Digit Quantity:

8

Display Units Indicator:

Included

Display Positioned Decimal Point:

Provided

Display Storage Facility:

Not included

Remote Control Provisions:

Not included

Solid State Feature:

Not included

Inclosure Material And Location:

Any acceptable

Plug-in Units Provision:

Included

Standard Frequency Output Feature:

Not included

Phase:

Two

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T297-a