

View Online at <https://aerobasegroup.com/nsn/6625-01-360-3926>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

1.875 inches

Overall Height:

3.000 inches

Overall Width:

3.000 inches

Mounting Stud Length:

0.750 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

4.240 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud bolt circle

Frequency Response Range:

+25.000/+1000.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.500 inches

Meter Body Diameter Behind Mounting Flange:

2.795 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+2.5 amperes, rf single indicator single range

Mounting Stud Diameter:

0.138 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Nomenclature wide-vue rf ammeter; 3 1/2 inch square face; measurement range (mrc bhmw) 0 to 2.5 amps, impedance ly 0.10 amps

Material:

Plastic phenolic

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0