

View Online at <https://aerobasegroup.com/nsn/6625-01-360-5177>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Stud Length:

Between 3.750 inches and 6.250 inches

Overall Diameter:

4.600 inches

Mounting Bolt Circle Diameter:

4.125 inches

Furnished Items And Quantity:

Nut 8; washer 8; sorder lug 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Green single indicator single range and red single indicator single range and yellow single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

3.850 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0 through 70 deg; 10 and 42 deg; off

Mounting Facility Type And Quantity:

6 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Mounting Stud Diameter:

0.250 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Forward

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Elec, elect. Properties and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0