

View Online at <https://aerobasegroup.com/nsn/6625-01-361-0640>

Circuit Current For Which Designed:

Dc

Overall Length:

4.635 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.800 inches

Overall Height:

1.900 inches

Overall Width:

4.215 inches

Mounting Hole Diameter:

0.190 inches

Shortest Vertical Distance Between Mounting Centers:

1.900 inches

End Application:

4920-01-148-5491 adapter kit, engine test

Indicator Type:

Digital display

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud rectangular/square

Meter Depth Behind Mounting Flange:

4.000 inches

Meter Body Width Behind Mounting Flange:

3.575 inches

Power Source:

External

Mounting Facility Type And Quantity:

6 unthreaded hole

Display Type:

Light emitting diode

Display Digit Quantity:

3-1/2

Measurement Range:

+0.0/+2.0 volts, dc single indicator 1st range+0.0/+20.0 volts, dc single indicator 2nd range+0.0/+200.0 volts, dc single indicator 3rd range+0.0/+500.0 volts, dc single indicator 4th range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.000 inches

Features Provided:

Autoranging and overranging and zero adjuster

Accuracy Rating:

Porm 0.008 pct porm One digit single indicator all ranges

Display Color:

Red single indicator all ranges

Circuit Attachment Method And Quantity:

37 pin

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0