NSN 6625-01-364-4508

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-364-4508

Circuit Current For Which Designed: Ac **Dielectric Withstanding Voltage In Volts:** 3000.0 **Overall Length:** 2.650 inches Scale Division Quantity: 20 single indicator single range **Frequency Rating:** 400.0 hertz Mounting Stud Length: 0.500 inches **Overall Diameter:** 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches **Indicator Type:** Dial w/pointer Installation Design: Panel **Mounting Arrangement Style:** Three hole/stud bolt circle **Frequency Response Range:** +360.000/+440.000 hertz **Sensitivity Rating:** 2.5 volt-amperes **Dial Scale Marking Color:** Black single indicator single range **Accuracy In Percent:** -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving iron vane **Background Color:** White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External

NSN 6625-01-364-4508

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+10.0 milliamperes, ac single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Luminous scale marking and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud and 2 solder lug

Phase:

Single

Special Features:

Ruggedized

Material:

Steel

Surface Treatment:

Enamel semigloss

Style Designator:

C1 round flush mtg

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-10304/7 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A310a0