

View Online at <https://aerobasegroup.com/nsn/6625-01-372-9161>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

11.000 inches

**Overall Height:**

5.250 inches

**Overall Width:**

8.475 inches

**Frequency Rating:**

Between 48.0 hertz and 440.0 hertz

**End Application:**

An/usm-603 ets

**Indicator Type:**

Digital display and dial w/pointer

**Installation Design:**

Bench

**Frequency Response Range:**

+0.001/+18.000 gigahertz

**Background Color:**

Black single indicator single range

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

4

**Measurement Range:**

-70.0/+44.0 decibels single indicator single range

**Scale Selection Method:**

Switch

**Accuracy Rating:**

Porm 1.2 pct of reading single indicator single range

**Display Color:**

White single indicator single range

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 240.0 ac

**Interface Compatibility:**

ieee-488

**Phase:**

Single or three

**Special Features:**

Option 004 deletes the standard five foot cable. Option 022 is digital input/output, fully compatible with hpinterfac (hp-ib) . Option hp11730b addsthe 10 foot cable to replace the standard five foot cable

**Style Designator:**

Rectangular or square

**Supplementary Features:**

Unit weight 10.0 pounds

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0