

View Online at <https://aerobasegroup.com/nsn/6625-01-372-9161>

Circuit Current For Which Designed:

Ac

Overall Length:

11.000 inches

Overall Height:

5.250 inches

Overall Width:

8.475 inches

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

End Application:

An/usm-603 ets

Indicator Type:

Digital display and dial w/pointer

Installation Design:

Bench

Frequency Response Range:

+0.001/+18.000 gigahertz

Background Color:

Black single indicator single range

Display Type:

Light emitting diode

Display Digit Quantity:

4

Measurement Range:

-70.0/+44.0 decibels single indicator single range

Scale Selection Method:

Switch

Accuracy Rating:

Porm 1.2 pct of reading single indicator single range

Display Color:

White single indicator single range

Operating Voltage Rating In Volts:

Between 100.0 ac and 240.0 ac

Interface Compatibility:

ieee-488

Phase:

Single or three

Special Features:

Option 004 deletes the standard five foot cable. Option 022 is digital input/output, fully compatible with hpinterfac (hp-ib) . Option hp11730b addsthe 10 foot cable to replace the standard five foot cable

Style Designator:

Rectangular or square

Supplementary Features:

Unit weight 10.0 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0