

View Online at <https://aerobasegroup.com/nsn/6625-01-379-5331>

Circuit Current For Which Designed:

Ac

Overall Depth:

4.500 inches

Overall Length:

9.625 inches

Overall Width:

5.625 inches

Scale Division Quantity:

30 single indicator 1st range

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Furnished Items And Quantity:

Handle 1; rechargeable ni cad batteries 2; shielded, foam-lined carrying case designed to hold up to 4 probes; manual; ac line cord; 8723 type probe

Indicator Type:

Dial w/pointer

Installation Design:

Hand held

Frequency Response Range:

+0.300/+40.000 gigahertz

Sensitivity Rating:

30.0 decibels

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator all ranges

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+3.0/+300.0 inches single indicator 2nd range

Scale Selection Method:

Switch

Features Provided:

Internal battery accommodation and portable and warning feature and zero adjuster

Operating Voltage Rating In Volts:

Between 110.0 ac and 220.0 ac

Phase:

Single

Special Features:

Operating temp m10 degrees c-p50 degrees c; weighs 4.5 lbs w/o case & probe; probe is 13.0 in. Lg including 2.125 in. Cup & has 4 ft. Lg cable

Functional Description:

Performs measurements iaw/ansi & fcc recommendations for radiation monitoring test equipment

Style Designator:

Hand-held

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0