

View Online at <https://aerobasegroup.com/nsn/6625-01-379-5531>

Width:

330.0 millimeters

Length:

456.0 millimeters

Ac Voltage Rating:

100.0 volts and 120.0 volts and 220.0 volts and 240.0 volts

Dc Voltage Rating:

Between 11.0 volts and 28.0 volts

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Major Components:

Signal generator; audio generator; rf analyzer; af analyzer; oscilloscope; spectrum analyzer; tracking generator; opt 001-high stability timebase; opt 002-spectrum analyzer w/tracking generator; opt 003-hp-ib/rs-232/current measurement; opt 004-tone/digital signaling; opt 005-256 k ram memory; opt 910-extra operating/quick reference manual (08920-90010 & 08920-90012)

Electrical Power Source Relationship:

Operating

Internal Battery Accommodation:

Not included

Inclosure Feature:

Single item w/housing

Test Type For Which Designed:

Rf frequency; am & fm modulation; audio frequency; ac/dc voltage; sinad/distortion

Operating Test Capability:

Rf freq 250 khz-1 ghz; am: 20 hz-25 khz, fm: dc to 75 khz; audio freq: dc to 25 khz; ac voltage: 0-30 v rms, dc voltage: 0.1-42.0 v; sinad range: 0-60 db; distortion range: 0.1-100.0 pct

Phase:

Single

Height:

188.0 millimeters

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T228-a