

View Online at <https://aerobasegroup.com/nsn/6625-01-379-9099>

Overall Length:

19.250 inches

Overall Height:

6.400 inches

Overall Width:

14.250 inches

Vibration Resistance Range In Hertz:

+5.0/+55.0

Vibration Resistance Amplitude:

0.003 inches total excursion

Shock Resistance Rating In Gravitational Units:

20.0

Operating Temperature Range:

+10.0/+40.0 degrees celsius

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

4600.0 meters

Inclosure Type:

Encased

Installation Design:

Top of cabinet/counter

Circuit Construction Type:

Solid state

Frequency Per Channel:

0.01 kilohertz operating channel and 250000.00 kilohertz operating channel

Indicator Device Type And Quantity:

1 cathode ray tube

Operating Ac Frequency In Hertz:

48.0 2nd voltage and 63.0 2nd voltage

External Ac Operating Voltage In Volts:

90.0 1st voltage and 127.0 1st voltage

Phase:

Single

Special Features:

Synthesized waveshapes are sine, square, triangle, ramp, pulse, arbitrary, & dc; operating modes: continuous, triggered, gated, burst waveform advance, & autostep; programmable interface gpib--ieee-488.2-1987 compatible; current-5 amps; power dissipation-300 watts; recommended adjustment interval--1000 hours or 6 months, whichever occurs first; original name was "generator, arbitrary"

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200