

View Online at <https://aerobasegroup.com/nsn/6625-01-386-8852>

**Terminal Quantity:**

1 and 5

**Terminal Type:**

Connector and binding post

**Overall Depth:**

24.800 inches

**Overall Height:**

7.000 inches

**Overall Width:**

17.000 inches

**Ac Voltage Rating:**

110.0 volts and 220.0 volts

**Frequency Rating:**

60.0 hertz

**Portability:**

Nonportable

**Unit Type:**

Encased

**Output Voltage Rating:**

Between 0.0 volts and 7.0 volts

**Electromotive Force Production Method:**

Electronic

**Output Accuracy Rating In Percent:**

-0.010/+0.010

**Warm-up Time For Maximum Accuracy In Minutes:**

30.0

**Protective Device Type:**

Fuse

**Criticality Code Justification:**

Supp

**Phase:**

Single

**Special Features:**

Frequency range 10hz to 1mhz: voltage range 700uv to 1000v: traceable to national standards: 24ppm total uncertainty: automatic ac measurement: compatible with fluke a40 and a40a current shunts: power up self test: 4 sets of input terminals, 1 n type and 1 set of binding post dedicated for ac measurements and transfer modes. 2nd set of binding posts are for current shunts: digital display shown in ppm, pct, volts and ratios. 1200v input protection on all ranges. Gpib/ieee488, rs232c interfaces are included

**Supplementary Features:**

5790a/af-opt03 is checked and verified by the aerospace guidance and metrology center before being shipped to the pmel labs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T263-k