

View Online at <https://aerobasegroup.com/nsn/6625-01-393-7663>

**Width:**

17.240 inches

**Length:**

17.750 inches

**Dc Voltage Rating:**

100.0 volts and 120.0 volts and 220.0 volts and 240.0 volts

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Furnished Items:**

Rack mount w/ handles p/n 950043; line cord p/n 568106000; instructions manual p/n 98401400a; ciil firmware revisions 460dt and 461dt

**End Application:**

Radats an/gsm-370

**Internal Battery Accommodation:**

Not included

**Inclosure Feature:**

Single item w/housing

**Measurement Unit:**

Average power

**Input Frequency Range:**

+0.000/+110.000 gigahertz

**Radio Frequency Input Power Rating:**

40.0 watts

**Phase:**

Single

**Special Features:**

Opt 4 includes s/9 kit: 4300 mainframe, -06 internal tma; 4311 universal channel mouldle; 4312 thermocouple channel module (used only w/ thermocouple sensors); 4321 programmable calibrator 30 mhz; rack mount kit, line cord, and instruction manual; opt -5 ciil firmware revisions 460dt & 461dt

**Height:**

3.480 inches

**Supplementary Features:**

Power range minus 75 dbm to plus 50 dbm; range to 990 db with diode sensors and 50 db with thermocouple sensors; bnc rear panel connectors; output level is front panel/ieee bus selectable for linear or logarithmeic output 0 to 10 v; free run access time 25 ms per channel or 40 readings per sec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T228-f