

View Online at <https://aerobasegroup.com/nsn/6625-01-393-7663>

Width:

17.240 inches

Length:

17.750 inches

Dc Voltage Rating:

100.0 volts and 120.0 volts and 220.0 volts and 240.0 volts

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Furnished Items:

Rack mount w/ handles p/n 950043; line cord p/n 568106000; instructions manual p/n 98401400a; ciil firmware revisions 460dt and 461dt

End Application:

Radats an/gsm-370

Internal Battery Accommodation:

Not included

Inclosure Feature:

Single item w/housing

Measurement Unit:

Average power

Input Frequency Range:

+0.000/+110.000 gigahertz

Radio Frequency Input Power Rating:

40.0 watts

Phase:

Single

Special Features:

Opt 4 includes s/9 kit: 4300 mainframe, -06 internal tma; 4311 universal channel mouldle; 4312 thermocouple channel module (used only w/ thermocouple sensors); 4321 programmable calibrator 30 mhz; rack mount kit, line cord, and instruction manual; opt -5 ciil firmware revisions 460dt & 461dt

Height:

3.480 inches

Supplementary Features:

Power range minus 75 dbm to plus 50 dbm; range to 990 db with diode sensors and 50 db with thermocouple sensors; bnc rear panel connectors; output level is front panel/ieee bus selectable for linear or logarithmeic output 0 to 10 v; free run access time 25 ms per channel or 40 readings per sec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T228-f