NSN 6625-01-393-7824

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-393-7824

| Circuit Current For Which Designed: |
|---|
| Dc |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 3.850 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.537 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.537 inches |
| Overall Height: |
| 4.350 inches |
| Overall Width: |
| 4.350 inches |
| Mounting Hole Diameter: |
| 0.250 inches |
| Frequency Rating: |
| 50.0 hertz |
| Environmental Protection: |
| Water resistant |
| End Application: |
| Polar class ice breaker |
| Indicator Type: |
| Digital display |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Meter Depth Behind Mounting Flange: |
| 3.800 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.980 inches |
| Background Color: |
| Black single indicator single range |
| Scale Marking: |
| Diesel speed (rpm x 100) |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Display Type: |
| Liquid crystal |
| Display Digit Quantity: |

NSN 6625-01-393-7824

Special Scale Meter - Page 2 of 2

Yes - demil/mli

Fiig: A310a0



| Accuracy Rating: |
|--|
| Porm 0.1 pct single indicator single range |
| Display Color: |
| Black single indicator single range and silver single indicator single range |
| Circuit Attachment Method And Quantity: |
| 1 connector, plug |
| Operating Voltage Rating In Volts: |
| 5.0 dc |
| Phase: |
| Single |
| Material: |
| Plastic |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |