

View Online at <https://aerobasegroup.com/nsn/6625-01-395-0571>

Wattage Rating In Watts:

150.0

Current Type:

Ac

Frequency Rating:

Between 40.0 hertz and 400.0 hertz

Electrical Connection Type:

Connector receptacle

Internal Battery Accommodation:

Not included

Voltage Rating:

Between 100.0 volts and 240.0 volts

Electrical Connection Quantity:

3

Measurement Type:

Frequency and time interval

Frequency Range:

+0.000/+26.500 gigahertz f1 input ratio

Accuracy Rating:

Porm 20 ns plus timebase uncertainty x measurement porm lsd

Gate Time:

Between 200.0 microseconds and 1000.0 microseconds

Internal Calibration Feature:

Included

Display Type:

Light emitting diode

Display Digit Quantity:

12

Display Units Indicator:

Included

Display Positioned Decimal Point:

Provided

Display Storage Facility:

Included

Remote Control Provisions:

Not included

Solid State Feature:

Included

Phase:

Single

Special Features:

Opt 26 26.5 ghz freq extension

Functional Description:

Designed for pulse and cw performance; six separate pulse microwave measurements to characterize signals: freq, prf, pri, pulse width, off-time & frequency profiling

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T297-a