

View Online at <https://aerobasegroup.com/nsn/6625-01-395-4062>

Overall Length:

13.000 inches

Overall Height:

6.500 inches

Overall Width:

13.000 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Frequency Range Rating:

+0.250/+1000.000 megahertz

End Application:

Common test equip

Output Impedance Rating:

50.0 ohms

Voltage Rating:

Between 90.0 volts and 264.0 volts

Modulation Type:

Fm

Crystal Controlled Feature:

Provided

Maximum Signal Output:

10 mhz greater than 0.5 volts level into 50 ohms

Modulator Location:

Any acceptable

Special Features:

Amplitude accuracy of porm 1.5 dbw/typical performance of porm 1 db to ensure accurate receiver sensitivity; low rf leakage assures proper testing of very sensitive devices; ultra stable dc fm w/porm 500 hz carrier frequency accuracy for testing pagers; resolution: 10 hz; accuracy: typically porm 3x10e6xcarrier frequency in hz; switching speed: less than 120 ms; spectral purity at 500 mhz; operating temperature: 0 to 50 deg. C; internal diagnostics; 300 storage registers; modulation: frequency-internal-400 hz or 1 khz, external-dc to 75 khz; phase-internal-400 hz or 1 khz, external-20 hz to 10 khz; amplitude-internal-400 hz or 1 khz, external 20 hz to 25 khz; hp-ib-ieee-488 interface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-j