NSN 6625-01-395-6149

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-395-6149

| Circuit Current For Which Designed: |
|---|
| Ac |
| Dielectric Withstanding Voltage In Volts: |
| 1500.0 |
| Overall Length: |
| 7.730 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 6.050 inches |
| Overall Height: |
| 1.530 inches |
| Overall Width: |
| 6.700 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Mounting Stud Length: |
| 0.750 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 10.0 ohms |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 6.130 inches |
| Meter Body Width Behind Mounting Flange: |
| 4.900 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Red single indicator single range |
| Scale Marking: |

ocale marking.

Percent, 0, 20, 40, 60, 80, 100

NSN 6625-01-395-6149

Arbitrary Scale Meter - Page 2 of 2



| Mounting Facility Type And Quantity: |
|---|
| 4 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Mounting Stud Diameter: |
| 0.221 inches |
| Meter Body Height Behind Mounting Flange: |
| 1.225 inches |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Tank 6-382-3-f fuel oil storage-ref |
| Material: |
| Steel |
| Surface Treatment: |
| Paint |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |