

View Online at <https://aerobasegroup.com/nsn/6625-01-398-1445>

Accessory Components And Quantity:

2 hp10441a 10: 1 probes. 1 miniature probe to bnc male adapter, 7.5 ft. Power cord, front panel reference and programming reference set, service manual

Mounting Method:

Table

Screen Size:

3.0 by 3.75 in.

Sweep Circuits:

Included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.0/+300.0 megahertz

Single Trigger Sweep Duration:

1.0 nanoseconds and 5.0 seconds

Trigger Sweep Polarity Switch:

Not included

Special Features:

Switchable bandwidth limits: ac coupled (lower -3db freq): 10 hz; If reject (lower -3db freq): 400 hz; bandwidth limit (upper -3db freq): 30 mhz; 2 channels; 1 mv/div to 5v/div vertical sensitivity range, vert. Gain accuracy: porm 1.25 pct. Of full scale; vert. Resolution: 8 bits over 8 div (porm 4 pct.), 10 bits via hpib w/averaging (porm 0.1 pct.) ; max. Sample rate: 1 gs a/s; waveform record lgth: 8001 pts real time, 501 repetitive; input coupling: ac, dc; autoscale feature; 17 automatic pulse paramenter measurements; waveform storage; external trigger functions: glitch, edge, pattern, state, dig. Delay x time/event, tv, time qual. Pattern

Functional Description:

Measrmnt stats, limit test, post acquisition, pan/zoom

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-g