

View Online at <https://aerobasegroup.com/nsn/6625-01-398-2781>

Overall Length:

16.750 inches

Wattage Rating In Watts:

60.0

Overall Height:

3.500 inches

Overall Width:

14.000 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Accessory Component Quantity:

2

End Application:

An/apm-233

Electrical Connection Type:

Bnc

Voltage Rating:

Between 100.0 volts and 240.0 volts

Electrical Connection Quantity:

2

Unpackaged Unit Weight:

26.000 pounds

Mounting Method:

Rack

Measurement Type:

Frequency

Frequency Range:

+0.001/+20.000 gigahertz

Accuracy Rating:

Porm 1 count plus timebase error

Gate Time:

Between 1.0 seconds and 1.0 microseconds

Sensitivity Rating:

25 mv rms

Display Type:

Light emitting diode

Display Digit Quantity:

12

Display Units Indicator:

Included

Display Positioned Decimal Point:

Provided

Display Storage Facility:

Included

Solid State Feature:

Not included

Phase:

Single

Special Features:

Kopt 2 measures power of signals & allows power offsets from m99.9 db to 99.9 db; opt 4 high stability time bases; opt 8 gpib ieee 488-1978 (standard in model 575b); opt wb83 includes slide, bracket support, rack mount, spacer & hardware; front panel selected service diagnostics/user info; sample rate from 100 msec to 10 sec hold position; reset, offset, and multiply functions; operating temp 0 to 50 degrees c; resolution .1 khz to 1 ghz; power cord & oper manual included

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T297-a