

View Online at <https://aerobasegroup.com/nsn/6625-01-398-5150>

End Application:

F-15e electronic test station

Unit Type:

Multimeter

Special Features:

6.5 digits; 7 functions: dc voltage (90 day, tcal porm 5 deg. C) voltage range: 250 volts/30 mv; dc current: (90 day, tcal porm 5 deg. C) range-1.5 amps/300 ua; resistance: (2 and 4 wire ohms)(90 day, tcal porm 5 deg. C) range-3 gigohms/30 ohms; ac voltage: (rms ac and rms ac/dc) range-300v/30mv, acv bandwidth: 20hz/1mhz, crest factor 3.5 to 1 at fullscale, common mode rejection: with 1 kohm imbalance in the low lead, dc to 60 hz, guarded-greater than 86db, nonguarded-greater than 66db, ac volts (90 day, tcal porm 5 deg. C); ac current: (rms ac and rms ac + dc) acl bandwidth: 20 hz to 100 khz, crest factor-3.5 to 1 at full scale, frequency: range-10 hz/1.5 mhz (voltage input), 10 hz/100 khz (current input), period: range-0.1 s/667 ns (voltage input), 0.1 s/3.33 us (current input); sensitivity: 10 mv rms or 100 ua rms (sinewave) ; triggering: triggers/counts on zero crossings; suffix a-solder lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T228-b