NSN 6625-01-400-0686

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-400-0686

| Overall Depth: |
|---|
| 17.500 inches |
| Overall Height: |
| 5.400 inches |
| Overall Width: |
| 15.000 inches |
| Current Type: |
| Ac |
| Voltage Rating: |
| Between 95.0 volts and 250.0 volts |
| Beam Quantity: |
| 2 |
| Screen Size: |
| 8 by 10 centimeters |
| Sweep Circuits: |
| Included |
| Generator Driven Feature: |
| Included |
| Sweep Circuit Type: |
| Horizontal and vertical |
| Sweep Frequency Range: |
| +5.0/+60.0 megahertz |
| Single Trigger Sweep Duration: |
| 20.0 milliseconds |
| Trigger Sweep Voltage Amplitude Rating: |
| Between 40.0 millivolts and 150.0 millivolts |
| Trigger Sweep Polarity Switch: |
| Not included |
| Trigger Sweep Marker Intervals: |
| 0.5 sec/div and 50 sec/div |
| Amplifier Deflection Sensitivity Provision: |
| Provided |
| Vertical Deflection Sensitivity Voltage Rating: |
| 2.0 millivolts peak to peak per centimeter |
| Horizontal Deflection Sensitivity Voltage Rating: |
| 5.0 volts any acceptable megahertz |
| Input Intensity Modulation Feature: |
| Not provided |
| Plate Direct Connection Deflection Sensitivity Provision: |
| Not provided |
| Frequency Response Rating: |
| Provided |
| |

NSN 6625-01-400-0686

Oscilloscope - Page 2 of 2



Z-axis Frequency Response Rating: 5.0 megahertz Amplifier Input Impedance Rating Provision: Provided X-axis Input Impedance Rating: 1.0 megohms **Calibrated Screen Scale:** Included Trace Storage Tube: Included Camera Recording Device Accommodation: Provided Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T320-g