

View Online at <https://aerobasegroup.com/nsn/6625-01-408-1448>

**Ac Voltage Rating:**

Between 105.0 volts and 125.0 volts

**Frequency Rating:**

Between 47.0 hertz and 420.0 hertz

**Major Components:**

Transmitter sr920770-10; two cableassy sr920752-10; two antenna assembly sr920751-10; receiver sr920760-10; two antenna supports sr920753-10

**End Application:**

5411-01-382-5833, milstar shelter, p/n ef920000-10

**Electrical Power Source Relationship:**

Operating

**Internal Battery Accommodation:**

Included

**Inclosure Feature:**

Multiple item w/housing

**Test Type For Which Designed:**

Insertion loss

**Phase:**

Single

**Special Features:**

Portable; operates at 920 mhz withtransmitted power of 2 watts/34 dbm; transmitted signal can be modulated or continuous wave; adjustable modulation frequency from 250hz to 1.6 khz; receiver receives signals attenuated up to 112 db or more; receiver provides adjustable audio tone; antennas have type n female connectors

**Functional Description:**

Monitors the insertion loss of a shielded volume, monitors integrity, & locates leaks in the shield

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T228-a