

View Online at <https://aerobasegroup.com/nsn/6625-01-417-3234>

Overall Length:

629.0 millimeters

Overall Height:

175.0 millimeters

Overall Width:

457.0 millimeters

Frequency Rating:

48.0 hertz and 66.0 hertz

Frequency Range Rating:

+0.010/+26.500 gigahertz

End Application:

An/alm-246

Voltage Rating:

Between 115.0 volts and 220.0 volts

Modulation Type:

Am and pulse

Calibrated Signal Output Range:

Minus 110 dbm to plus 20 dbm

Modulator Location:

Internal

Modulated Frequency Rating:

Between 0.1 megahertz and 8.0 megahertz

Phase:

Single

Functional Classification:

Bb-1.1

Special Features:

Xmax leveled power plus 10 dbm; resolution 1 hz; opt 001 step attenuator, opt 006 fast pulse modulation, opt 008 1 hz freq resolution, opt 700 mate system compatibility, opt h43 tiss special configuration; rf output connector 3.5 mm

Functional Description:

Used to drive hp 83550 series millimeter-wave modules; provide test signals; can drive source modules throughhp 8349b amplifier

Reference Data And Literature:

To 33d7-38-251-4

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-j