

View Online at <https://aerobasegroup.com/nsn/6625-01-422-2485>

**Width:**

18.800 inches

**Ac Voltage Rating:**

110.0 volts and 220.0 volts

**Dc Voltage Rating:**

Between 22.0 volts and 30.0 volts

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Depth:**

25.000 inches

**End Application:**

Multi-acft

**Electrical Power Source Relationship:**

Operating

**Inclosure Feature:**

Single item w/housing

**Test Type For Which Designed:**

Radio communications maintenance

**Operating Test Capability:**

Rfsignal generator freq range 500k to 1 ghz in 100hz steps; receiver 500k to 1ghz; audio generator 10hz to 40khz; spectrum analyzer 500k to 1 ghz; digitiged oscope input ranges of 2 millivolt to 50v/div w/max input of 200v

**Special Features:**

Accessories included c/o flexible antenna, dc shunt, 20db pad, 10db pad, dc power cord, ac power cord, dmm probes, scope probe, extra fuses

**Height:**

7.400 inches

**Supplementary Features:**

This test set is a version of thefm/am 1600 base unit. The dash 3 indicates this unit as capable of accepting the j-1601 or j-1603 life support application unit which supports the four lrus prc-112, prc-90, prc-90a, urt-33

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T228-a