

View Online at <https://aerobasegroup.com/nsn/6625-01-422-2485>

Width:

18.800 inches

Ac Voltage Rating:

110.0 volts and 220.0 volts

Dc Voltage Rating:

Between 22.0 volts and 30.0 volts

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Depth:

25.000 inches

End Application:

Multi-acft

Electrical Power Source Relationship:

Operating

Inclosure Feature:

Single item w/housing

Test Type For Which Designed:

Radio communications maintenance

Operating Test Capability:

Rfsignal generator freq range 500k to 1 ghz in 100hz steps; receiver 500k to 1ghz; audio generator 10hz to 40khz; spectrum analyzer 500k to 1 ghz; digitiged oscscope input ranges of 2 millivolt to 50v/div w/max input of 200v

Special Features:

Accessories included c/o flexible antenna, dc shunt, 20db pad, 10db pad, dc power cord, ac power cord, dmm probes, scope probe, extra fuses

Height:

7.400 inches

Supplementary Features:

This test set is a version of thefm/am 1600 base unit. The dash 3 indicates this unit as capable of accepting the j-1601 or j-1603 life support application unit which supports the four lrus prc-112, prc-90, prc-90a, urt-33

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T228-a