

View Online at <https://aerobasegroup.com/nsn/6625-01-433-6365>

Circuit Current For Which Designed:

Dc

Overall Length:

2.700 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

50 single indicator single range

Overall Diameter:

4.560 inches

Environmental Protection:

Cold resistant and dust resistant and fungus proof and humidity proof and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

4.125 inches

Furnished Items And Quantity:

Lock washers 10, flat washers 10, nuts 10, mounting screws 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.450 inches

Meter Body Diameter Behind Mounting Flange:

3.630 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

0 1 2 3 4 5; six major and 45 minor calibration lines just above the numbers on the scale

Mounting Facility Type And Quantity:

6 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Self-illumination facility

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Below the scale is range of operation, "tension lbs x 1000"

Style Designator:

C1 round flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0