

View Online at <https://aerobasegroup.com/nsn/6625-01-434-7690>

**Circuit Current For Which Designed:**

Ac and dc

**Overall Length:**

15.675 inches

**Overall Height:**

3.500 inches

**Overall Width:**

8.375 inches

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**End Application:**

Electr test equipment

**Indicator Type:**

Digital display

**Installation Design:**

Bench

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

5-1/2

**Measurement Range:**

+0.0/+2.0 milliamperes, dc single indicator all ranges

**Features Provided:**

Extension cable

**Accuracy Rating:**

Better than 0.6 pct for readings between 1 kohm & 1 tohm;  $\sqrt{i}$  ohms accuracy equals voltage source plus ammeter accuracy single indicator all ranges

**Display Color:**

Black single indicator all ranges

**Circuit Attachment Method And Quantity:**

Binding post

**Phase:**

Single

**Special Features:**

Programmable porm 500 v source with 10 mv resolution and 50 v range with 1mv resolution; also called picoammeter/voltage source; 3 intensi type 10 char display; trigger delay; bnc & 3 lug connectors; stores up to 512 readings, reading interval 10 ms to 999. Sec

**Functional Description:**

Pmt current, mass spectrometer current & probe current measurements; plasma generated currents, ion chamber currents

**Style Designator:**

Rectangular surface mtg

**Unit Of Issue Weight:**

9.30 pounds

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0