

View Online at <https://aerobasegroup.com/nsn/6625-01-447-3848>

Ac Voltage Rating:

115.0 volts and 230.0 volts

Dc Voltage Rating:

28.0 volts

Frequency Rating:

60.0 hertz

Major Components:

Control panel; gridcase 80386 processor laptop computer; operating manual; cables; terminators; sma/bnc adapter; antenna; ground plane antenna

Electrical Power Source Relationship:

Operating

Internal Battery Accommodation:

Included

Material And Location:

Aluminum carrying case

Inclosure Feature:

Multiple item w/carrying case

Test Type For Which Designed:

Ranging; short communications; extended communications uplink; extended communications downlink

Operating Test Capability:

Rf attenuator range 1-127 db incremented range; output power 28 vdc for for uut

Special Features:

Requested name high accuracy test set; control panel c/o the laptop computer, power, rf, & interface connectors, power select, interrupt switches, rf output select switch, power light indicators, circuit breaker/fuse, variable attenuator, test jacks; laptop is ibm at ms-dos compatible, contains a 80386 processor, 3.6 mb ram, 1.4 mb 3.5 in. Floppy drive, 10 in. Diagonal backlit lcd monitor

Functional Description:

Computer controlled tester capable of interrogating a transponder unit under test

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T228-a