

View Online at <https://aerobasegroup.com/nsn/6625-01-457-6415>

**Circuit Current For Which Designed:**

Ac and dc

**Overall Length:**

14.000 inches

**Overall Height:**

7.000 inches

**Overall Width:**

8.500 inches

**Frequency Rating:**

Between 40.0 hertz and 1000.0 hertz

**Furnished Items And Quantity:**

Millivac ug-201 input test lead-bnc connector, 3 ft shielded cable and 2 color-coded alligator clips for dc, ac, and ohms measurements; ac line power cord; instruction manual

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Bench

**Accuracy In Percent:**

-6.0/+6.0 at full scale 2nd indicator 3rd range

**Power Source:**

External and internal

**Scale Graduation Type:**

Nonlinear all indicators all ranges

**Measurement Range:**

+0.0/+100.0 kilohertz 3rd indicator single range

**Scale Selection Method:**

Switch

**Operating Voltage Rating In Volts:**

Between 115.0 ac and 230.0 ac

**Special Features:**

Nicad rechargeable battery

**Functional Description:**

This unique, highly sensitive, and versatile multifunctional solid-state precision test instrument is suited for a variety of dc, ac, rf, and ohms measuring applications

**Style Designator:**

D1 rectangular or square

**Supplementary Features:**

3 different scales, 1st scale is ac volts, 2nd scale is rf volts, 3rd scale is ac amps; connectors-ac and dc input, bayonette type bnc; rf input-6 pin amphenol; dc output-2 color-coded binding posts; ac power-3 pin grounded

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0