

View Online at <https://aerobasegroup.com/nsn/6625-01-458-5859>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

3.125 inches

Overall Length:

7.000 inches

Overall Width:

5.250 inches

Scale Division Quantity:

50 single indicator 2nd range

Environmental Protection:

Dust resistant and humidity resistant and vibration resistant

Furnished Items And Quantity:

Btry 2; color-coded test leads 2; screw-on clips 2; instruction manual 1

Indicator Type:

Dial w/pointer

Installation Design:

Bench or hand held

Sensitivity Rating:

5.0 kilohm per volt and 20.0 kilohm per volt

Dial Scale Marking Color:

Green, light single indicator 1st range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator 9th range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External and internal

Scale Graduation Type:

Nonlinear single indicator 5th range

Measurement Range:

+0.0/+500.0 milliamperes, dc single indicator 7th range

Scale Selection Method:

Switch and terminal

Features Provided:

Electrical overload protection and internal battery accommodation and internal shunting and mirror scale and portable and rectifier circuit and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 banana jack and 2 banana plug

Operating Voltage Rating In Volts:

Between 1.5 dc and 9.0 dc

Special Features:

LACK-SO-VER-LOAD

Special Markings:

Black-sign, red + sign, below bottom scale

Material:

Plastic phenol-formaldehyde

Style Designator:

Portable

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0